







## **FEATURES**

- > Easy to maneuver with 210° turning radius.
- ➤ All pivot points are greased to ensure excellent maneuverability with effortless steering.
- > Speed lowering valve can adjust the descent speed freely.
- Foot and hand control the lowering function to ensure easy operation.
- Excellent and compact design pump with high pressure relief valve to prevent overload.

## HAND PALLET TRUCK

Economic and effortless solution for loading and unloading heavy goods. The ideal storage aid and handling partner for all manual transport tasks over short distance. Integral casting oil pump, original imported seal. Whole valve core. Strong & durable. Integrated process & automatic welding which increased the strength to 25% to ensure the normal use of deformation of the lower fork lever. The rotating parts are assembled with an alloy lining which can absorb partial load, wear resistance and prolong service life.



TECHNICAL PARAMETERS					
Product Code	LHPT	2054	2554/2568	3054/3068	5068
Capacity	kg	2000	2500	3000	5000
Minimum Fork Height	mm	85	85	85	85
Maximum Fork Height	mm	200	200	200	200
Maximum Lifting Height	mm	≥110	≥110	≥110	≥110
Fork Outside Width	mm	540	540/ 685	540/ 685	685
Fork Length	mm	1150	1150/1220	1150/1220	1220
Overall Length	mm	1550	1550/1620	1550/1620	1645
Overall Height	mm	1245	1245	1245	1235
Minimum Turning Radius	mm	1350	1350/1450	1350/1450	1445
Wheel Type	Nylon				
Approximate Weight	kg	65	68/73	72/78	130